

Ocean Technical Data

	Standard	Result
Tile Size (mm)		228.6 x 1219.2 mm (9" x 48")
Total Thickness (mm)		5.0 mm
Wear Layer Thickness (mm)		0.5 mm
Weight (±50 gr/m ²)	EN 430	8.3kg / m ²
Box Quantity		8 Planks / 2.232 m ²
Peeling Strength of Layer	EN 431	Pass
Impact sound reduction	ISO 140-7	L'nT,w 51
Dimension stability	EN 434	0.10%
Color fastness to light	ISO 105 B02	≥ Grade6
Static indentation	EN 433	≤ 0.1mm
Embossing	Regular/Deep	
Flexibility	EN 435	Pass
Abrasion resistance	EN 660-2	Class T
Castor chair resistance	EN 425	Pass
Slip resistance	AS 4586:2013	R10
Fire rating	AS. ISO 9239.1 2003	CFH: 8.7 kW/m ² Smoke Value: 208 % min
Usage category	EN 685	23/42
Resistance to chemical	EN 423	Pass
Electrostatic properties	EN 1815	< 2kv
Surface treatment		PUR
UL Environmental	UL 82386-4230	NSF/ANSI 332 - 2011 Silver - Sustainability Assessment for Resilient Floor Coverings
Environmental	Floor score (SCS-EC10.3-2014 v3.0)	Indoor Air Quality Certified; low VOC emissions
Adhesive	ISO 9001 : 2008	
Quality Control Mgmt		
Environmental Mgmt	ISO 14001 : 2004	



For more information  **1300 093 745**

Email info@decoline.com.au Visit www.decoline.com.au